

Viterra's port loading facilities

| | Outer Harbor | Inner Harbour | Port Lincoln | Wallaroo | Port Giles | Thevenard |
|--|---|--|---|--|---|---|
| Latitude | 34°51'S | 34°51'S | 34°43'S | 33°65'S | 35°05'S | 32°09'S |
| Longitude | 138°30'E | 138°30'E | 135°50'E | 137°37'E | 137°55'E | 133°39'E |
| Max. LOA | 320m | 225m | 270m | 200m | 225m | 180m |
| Max. beam | 36.0m | 32.2m | 30.0m | 32.0m | 32.2m | 28.0m |
| Depth alongside | 16.2m | 10.9m | 15.0m | 8.7m | 14.7m | 9.8m |
| Length of berth | 320m | 204m | 347m | 290m | 340m | 198m |
| Max. sailing draft | 14.0m | 9.3m plus tide | 14.6m plus tide | 8.5-9.0m | 14.7m | 9.0m |
| Ship loader type | Cleveland cascade chute travelling loader Trimming head attached to loader when hold trimming No. of belts: 1 No. of spouts: 1 | 1 travelling gantry loader Spout trimming only No. of belts: 1 No. of spouts: 1 | 2 travelling gantry loaders Spout trimming only No. of belts: 2 No. of spouts: 2 | 5 identical slewing loading booms with spouts attached (Operate 2 at a time) Spout trimming only No. of belts: 1 No. of spouts: 5 | 5 identical slewing loading booms with spouts attached No trimming heads available Spout trimming only No. of belts: 1 No. of spouts: 5 | 1 travelling gantry with retractable boom and spout attached No trimming heads available Spout trimming only No. of belts: 1 No. of spouts: 1 |
| Air draft | 24.4m | 14.7m | 22.3m | 12.9m | 15.5m | 14.0m |
| Indicative loading rate (metric tonnes/hour) | 2200tph | 800tph | 3000tph | 800tph | 1000tph | 1000tph |

For more information contact:

Western region

Port Lincoln
Phone: 08 8683 6100
Fax: 08 8682 6526

Central region

Balaklava
Phone: 08 8862 0200
Fax: 08 8862 0202

Adelaide region

Inner Harbour
Phone: 08 8114 2700
Fax: 08 8114 2791

Eastern region

Bordertown
Phone: 08 8595 9500
Fax: 08 8595 9510